

STANDARD DOCK BUMPERS AND ACCESSORIES

RESILIENT LAMINATED DOCK BUMPERS

Lathams Standard Resilient Horizontal Bumpers


Material/Thickness

- Fabric reinforced rubber pads cut from selected recycled truck tyres and belting
- Rubber pads laminated between structural steel angles and secured with 18mm steel tie rods

Installation

- Structural mounting angles permit welded installations or provide bolting through steel
- No assembly required

LATHAM STANDARD RESILIENT HORIZONTAL BUMPERS							LATHAM STANDARD RESILIENT VERTICAL BUMPERS					
All measurements in mm (approx)												
	Wt. kg	A	B	C	D	E		Wt. kg	A	B	C	D
LB410 — 14	15	280	150	250	350	400	LVB420 — 11	24	500	210	280	330
LB410 — 24	24	530	150	250	600	650	LVB430 — 11	35	750	210	280	330
LB410 — 36	36	830	150	250	900	950	LVB440 — 11	43	1000	210	280	330



Uses/Applications

- Comes in two models: bumpers with angles for most applications – equipped with 6mm steel angles on both ends; and bumpers with flat plate for use with dock levellers – optional 6mm flat steel plate for one or both ends.
- Have unlimited applications in factories, warehouses, docks
- Projecting above low docks
- Rub rails at the sides of truck wells
- Special construction features to accommodate unusual anchoring conditions
- Wall bumpers to protect against fork lift trucks

Specifications

- Supply and install Laminated Rubber Dock Bumpers as manufactured by Latham Australia, 14 Tennyson Road, Gladesville, NSW 2111. Ph: (02) 9879 7888 Fax: (02) 9879 7666. Model No.(s) _____ Resilient rubber material of bumpers shall be rubberised-fabric truck tyres and belting cut to uniform size pads, 115mm x 250mm and punched to receive 18mm supporting rods.
- All bumpers must be 115mm thick (projection from dock), and closed with two 75 x 63 x 6mm structural

steel angles. The angles are welded to 18mm rods at one end and closed with threaded rod and nut at the other end.

- The anchor leg of angle extends a minimum of 63mm beyond the rubber surface at either end and contain two 20mm anchor bolt holes as required. (Anchor bolts are supplied separately).
- The finish for exposed metal parts shall be painted or galvanised – (specify).

Anchor Accessories For Loading Dock Bumpers

