## **HHSAF Heavy Duty Series - Pedestrian**

Flexible Expansion Joint Cover

+/-25mm

All dimensions are in millimetres

25mm

7mm

## LATHAM AUSTRALIA PTY LTD

14 TENNYSON ROAD GLADESVILLE 2111 AUSTRALIA Phone: 61 2 9879 7888 Fax: 61 2 9879 7666 Web: www.latham-australia.com

Design subject to change without notice.



COPYRIGHT © 2009

LATH3513

This floor-to-wall detail can be used with other floor joint details like the NSA and NSS series expansion joint covers. Illustrated: HHSAF-50 Scale: Approx. Full Size They allow double the movement of standard floor-to-wall details. All dimensions are to be verified before construction Side member and support rail factory Verified By..... drilled to accept 8mm countersunk head Date..... fixings at approximately 350mm centres 6mm Aluminium Support Rail Shallow Block Out 25mm (Limited Flexibility) Optional BFG Suitably Water Gutter packed Exterior/Interior use. All mechanical expansion joint fixings by others. Stainless Total Available Overall Cover Plate Steel Code Movement Depth Thickness Aluminium fixed members with specified cover plate. The centering bar consists of Extra Heavy Duty elongated spherical rods fastened at opposite ends HHSAF-25 +25/-12mm 37mm 25mm 5mm +/-25mm 50mm 25mm 5mm of a flat spring steel bar. The bar is positioned diagonally across the joint opening with the elongated HHSAF-50 12 spheres inside the extruded suitable tracks. This unique concept allows for increased rotational HHSAF-75 +/-25mm 25mm movements and maintains constant spring tension at the centre of the cover plate. This greatly +/-25mm 50mm 25mm 6mm reduces the stresses on the embedded anchor sections and the surrounding concrete slabs. +/-25mm 25mm 6mm