

# SAA (FASM 64) Ultimate Series

Flexible Mechanical Expansion Joint Cover


**LATHAM AUSTRALIA PTY LTD**  
 14 TENNYSON ROAD GLADESVILLE 2111 AUSTRALIA  
 Phone: 61 2 9879 7888 Fax: 61 2 9879 7666  
 Web: www.latham-australia.com



Illustrated: SAA-55 (FASM 64) Scale: Approx. 90% Full Size

All dimensions are to be verified before construction

Verified By..... Date.....



Aluminium Code ribbed deck	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth	Cover Plate Thickness
SAA-30 (FASM 64)	30	182	100	40	35	101	+65/-20mm	85mm	64mm	3mm
SAA-55 (FASM 64)	55	207	125	40	35	101	+65/-45mm	110mm	64mm	3mm
SAA-80 (FASM 64)	80	232	150	40	35	101	+/-65mm	130mm	64mm	3mm
SAA-105 (FASM 64)	105	257	175	40	35	101	+/-65mm	130mm	64mm	3mm
SAA-130 (FASM 64)	130	282	200	40	35	101	+/-65mm	130mm	64mm	5mm
SAA-155 (FASM 64)	155	307	225	40	35	101	+/-65mm	130mm	64mm	5mm

All dimensions are in millimetres.

Exterior/Interior use.

All mechanical expansion joint fixings by others.

The centering bar consists of two full nylon spheres fastened at opposite ends of a flat spring steel bar. The bar is positioned diagonally across the joint opening with the spheres inside the extruded cylindrical tracks. This unique concept allows for increased rotational movements and maintains constant spring tension at the centre of the cover plate. This greatly reduces the stresses on the embedded anchor sections and the surrounding concrete slabs.

Design subject to change without notice.

COPYRIGHT © 2009

LATH3513