SLS (SSSM) Ultimate Series - Deep

Flexible Mechanical Expansion Joint Cover

LATHAM AUSTRALIA PTY LTD

14 TENNYSON ROAD GLADESVILLE 2111 AUSTRALIA Phone: 61 2 9879 7888 Fax: 61 2 9879 7666 Web: www.latham-australia.com

D



Illustrated: SLS-25 (SSSM 79) Scale: Approx. 90% Full Size

All dimensions are to be verified before construction

Verified By...... Date.....

Exterior/Interior use.

All mechanical expansion joint fixings by others.

Aluminium embedded members on continuous treated steel support with stainless steel cover plate.

Design subject to change without notice.

- ▲ Specify required depth i.e. SLS-25 (SSSM 79) Available depths: 54mm, 64mm, 79mm, 89mm, 104mm, 114mm, 139mm & 164mm.

Stainless Steel Code smooth deck	А	В	С	D	Е	F	Movement	Total Available Movement	Overall Depth	Cover Plate Thickness
SLS-25 (SSSM ▲)	25	56	38	18	13	•	+/-12mm	24mm	Specify	3mm
SLS-50 (SSSM ▲)	50	81	63	18	13	•	+/-12mm	24mm	Specify	3mm

475mm centres 14mm Wall member factory drilled to accept countersunk head 6.5mm 65mm (varies) fixings distance subject to required depth. Optional BFG Water Gutter COPYRIGHT © 2009 LATH3513 All dimensions are in millimetres.

Continuous treated

factory drilled with

10mm holes at

approximately

steel angle supports