

FXA Surface-Line Series - Standard


Flexible Expansion Joint Cover

LATHAM AUSTRALIA PTY LTD
 14 TENNYSON ROAD GLADESVILLE 2111 AUSTRALIA
 Phone: 61 2 9879 7888 Fax: 61 2 9879 7666
 Web: www.latham-australia.com



Illustrated: FXA-25 Scale: Approx. Full Size
 All dimensions are to be verified before construction

Verified By..... Date.....



Aluminium Code ribbed deck	A	B	C	D	E	F	Movement	Total Available Movement	Overall Depth	Cover Plate Thickness
FXA-25	25	146	75	49	20	18	+25/-15mm	40mm	Surface Mounted	3mm
FXA-50	50	171	100	49	20	18	+/-25mm	50mm	Surface Mounted	3mm
FXA-75	75	196	125	49	20	18	+/-25mm	50mm	Surface Mounted	4mm
FXA-100	100	221	150	49	20	18	+/-25mm	50mm	Surface Mounted	5mm
FXA-125	125	246	175	49	20	18	+/-25mm	50mm	Surface Mounted	5mm

Larger movement capabilities and wider joint widths available on request. All dimensions are in millimetres.

Exterior/Interior use.

All mechanical expansion joint fixings by others.

The centering bar consists of two elongated spherical rods fastened at opposite ends of a flat spring steel bar. The bar is positioned diagonally across the joint opening with the elongated spherical rods inside the extruded tracks. This unique concept allows for increased rotational movements and maintains constant spring tension at the centre of the cover plate. This greatly reduces the stresses on the embedded anchor sections and the surrounding concrete slabs.

Design subject to change without notice.

COPYRIGHT © 2019