




25S - Top View

25S - Bottom View





Aluminium Code	Α	В	С	Movement	Total Available Movement	Overall Depth
Type 25S	25	66	48	+/-25mm	50mm	6mm
Type 50S	50	106	48	+/-40mm	80mm	6mm
Type 75S	75	161	48	+/-65mm	130mm	6mm
Type 100S	100	161	48	+/-40mm	80mm	6mm



## **FEATURES**

- Aluminium wall & ceiling expansion joint cover.
- Suitable for fixing to masonry, timber, cement sheet, gyprock and other hard surfaced applications.

## **MATERIALS**

- Aluminium 6063-T5 mill finish alloy.
- Supplied in 3050mm lengths.
- Stainless steel spring clips.
- All visual surfaces come with a 20 micron clear anodised finish (contact a Latham representative for alternative anodising or powder coating options).

## **FIXINGS**

The joint clips onto the wall or ceiling with a pre-fixed locking mechanism (hidden from external view) at ~500mm centres.

## **FURTHER TECHNICAL SPECIFICATIONS**

- Website Link PDF and DWG Details
- **Product Information**
- Joint Specifications
- Fire Rated Systems
- Full Product Catalogue
- **Architectural Specifications**
- Warranty









e sales@latham-australia.com